

## Feuerwehrkarabiner Mousquetons pour pompiers



4300 - 4324



4328 - 4332



4340 - 4346



4358

Bestell cmde No	Einheit unité St/pcs	Stahl verzinkt acier zingué	Typ type	Länge longueur ca.mm	Draht fil ca.mm	Oese œillet ca.mm	Oeffnung ouverture ca.mm	Nutzlast charge utile ca. kg
4300	100		245	40,0	4,0	6,0	6,0	8
4302	100		245	50,0	5,0	8,0	6,0	30
4304	100		245	60,0	6,0	8,0	8,0	60
4306	50		245	70,0	7,0	10,0	9,0	90
4308	50		245	80,0	8,0	11,0	9,0	120
4310	50		245	90,0	9,0	12,0	12,0	140
4312	50		245	100,0	10,0	14,0	12,0	180
4316	25		245	120,0	11,0	13,0	15,0	250
4320	25		245	140,0	12,0	20,0	18,0	300
4322	25		245	160,0	13,0	22,0	25,0	350
4324	10		245	180,0	14,0	21,0	30,0	400
4328	100	mit Rundkausche		60,0	6,0	6,0	6,0	60
4330	50	avec cosse ronde		80,0	8,0	10,0	10,0	120
4332	25			100,0	10,0	14,0	12,0	180
4340	100	mit Schraubverschluss	245-S	60,0	6,0	8,0	6,0	120
4341	100	avec fermeture à vis	245-S	70,0	7,0	11,0	8,0	180
4342	50		245-S	80,0	8,0	12,0	8,0	230
4344	25		245-S	100,0	10,0	15,0	10,0	350
4346	20		245-S	120,0	11,0	18,0	14,0	450

Bestell cmde No	Einheit unité St/pcs	Aluminium eloxiert	Länge longueur ca.mm	Draht fil ca.mm	Oeffnung ouverture ca.mm	Bruchkraft charge de rupture ca. kg
4358	5	mit Sicherheitsverschluss avec fermeture de sécurité	120,0	12,0	23,0	1300